9001KM1

30mm Push Button, Types K, SK or KX, light module, transformer, 110/120 VAC





Main	
Range of Product	Harmony 9001K Harmony 9001SK
Product or Component Type	Light block
Device short name	9001K
Bulb base	BA 9s
Light block supply	Direct via integral transformer 6 V

Complementary

0.32 lb(US) (0.144 kg)	
Incandescent bulb	
120 V AC	
110120 V	
Via integral transformer	
5060 Hz	
30 mm	
	Incandescent bulb 120 V AC 110120 V Via integral transformer 5060 Hz

Environment

LIMIOIIIIEIL	
Protective treatment	TC
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)
IP degree of protection	IP20 IEC 60529
Standards	EN/IEC 60947-5-4 EN/IEC 60947-5-1 JIS C 4520 CSA C22.2 No 14 EN/IEC 60947-1 UL 508 JIS C 852
Product Certifications	UL 508 NEMA
Electrical shock protection class	Class II IEC 61140
Vibration resistance	7 gn 2500 Hz)IEC 60068-2-6
Shock resistance	50 gn IEC 60068-2-27

Ordering and shipping details

Category	21435-9001 KM LIGHT MODULES
Discount Schedule	CS1
GTIN	3389110918588
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.80 in (4.572 cm)
Package 1 Width	2.20 in (5.588 cm)
Package 1 Length	3.70 in (9.398 cm)
Package 1 Weight	5.28 oz (149.686 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	24
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	15.75 in (40.0 cm)
Package 2 Length	9.45 in (24.0 cm)
Package 2 Weight	8.43 lb(US) (3.825 kg)


Offer Sustainability

Green Premium product
WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
☐ REACh Declaration
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
China RoHS Declaration
€Yes
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

	•
11/2	40
vvarranty	18 months
•	

Dimensions



e panel thickness: 1 to 6 mm / 0.04 to 0.24 in.