



Main

Range	EasyLogic
Product name	EasyLogic PM2200
Device short name	PM2210
Product or Component Type	Power meter

Complementary

Device Application	Sub billing Power monitoring
Power quality analysis	Total harmonic distortion
Type of measurement	Apparent power min/max, total Active and reactive power min/max, total Current min/max, avg Voltage min/max, avg Frequency min/max, avg Total current harmonic distortion THD (I) per phase Total voltage harmonic distortion THD (U) per phase Power factor min/max, avg Apparent energy total Active and reactive energy total
Metering type	Voltage U, U21, U32, U13, V, V1, V2, V3 Unbalance current Calculated neutral current Apparent power S, S1, S2, S3 Peak demand currents Current I, I1, I2, I3 Active, reactive, apparent energy (signed, four quadrant) Active power P, P1, P2, P3 Reactive power Q, Q1, Q2, Q3 Peak demand power PM, QM, SM Demand power P, Q, S
Accuracy class	Class 1 active energy IEC 62053-21 Class 1 reactive energy IEC 62053-24
Measurement accuracy	Apparent power +/- 1 % Active energy +/- 1 % Reactive energy +/- 1 % Active power +/- 1 % Voltage +/- 0.5 % Power factor +/- 0.01 Current +/- 0.5 % Frequency +/- 0.05 %
Measurement current	5...6000 mA
Measurement voltage	35...480 V AC 50/60 Hz between phases 20...277 V AC 50/60 Hz between phase and neutral 480...999000 V AC 50/60 Hz with external VT
Frequency measurement range	45...65 Hz
[Us] rated supply voltage	44...277 V AC 45...65 Hz +/- 10 % 44...277 V DC +/- 10 %
Network Frequency	60 Hz 50 Hz

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ride-through time	100 Ms 120 V AC typical 400 Ms 230 V AC typical 50 ms 125 V DC typical
Line Rated Current	1 A 5 A
Maximum power consumption in VA	6 VA 277 V AC
Maximum power consumption in W	3.3 W power lines (AC)) 2 W 277 V power lines (DC))
Input impedance	Current <= 0.3 mOhm) Voltage > 5 MOhm)
Tamperproof of settings	Protected by access code
Display Type	Backlit LCD
Display colour	Monochrome
Display Resolution	128 x 128 pixels
Demand intervals	Configurable from 1 to 60 min
Information displayed	Demand current past value) Demand current present value) Demand power past value) Demand power present value) Voltage Current Frequency Energy consumption Harmonic distortion Power factor Active power Apparent power Reactive power Unbalanced in % Harmonic amplitude
Control type	4 x button
Local signalling	Red LED output signal 1...9999000 pulse/ k_h (kWh, kVAh, kVARh) Green LED module operating (RUN)
Number of inputs	0
Number of Outputs	1 pulse
POP parameter	20 ms 5...40 V DC, 20 mA 1...9999000 pulse/ k_h (kWh, kVAh, kVARh)
Impulse duration	20 ms
Communication port protocol	POP
Sampling rate	64 samples/cycle
Cybersecurity	Enable/disable communication ports
Communication Service	Remote monitoring
User Language	German English Chinese Russian Spanish Portuguese French
Product certifications	CE IEC 61010-1 CULus UL 61010-1 CULus CSA C22.2 No 61010-1 RCM EAC C-tick
Mounting Mode	Clip-on
Mounting position	Vertical
Mounting support	Framework
Provided equipment	1 x Installation guide
Measurement category	Category III 480 V Category II 480...600 V
Electrical Insulation Class	Class II Double insulation
Flame retardance	V-0 conforming to UL 94
Connections - terminals	Current transformer screw connection bottom) 6 Voltage inputs screw connection top) 4
Material	Polycarbonate

Width	3.78 in (96 mm)
Depth	Total 3.00 in (76.09 mm) Embedded 2.43 in (61.64 mm)
Height	3.78 in (96 mm)
Product Weight	10.58 oz (300 g)
Compatibility code	PM2210

Environment

Service Life	7 year(s)
IP degree of protection	Front IP54 IEC 60529 Body IP30 IEC 60529
Relative humidity	5...95 % 122 °F (50 °C)
Pollution degree	2
Ambient air temperature for operation	14...140 °F (-10...60 °C)
Ambient Air Temperature for Storage	-13...158 °F (-25...70 °C)
Operating altitude	<= 6561.68 ft (2000 m)
Electromagnetic compatibility	Electrostatic discharge IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test IEC 61000-4-3 Electrical fast transient/burst immunity test IEC 61000-4-4 Surge immunity test IEC 61000-4-5 Conducted RF disturbances IEC 61000-4-6 Magnetic field at power frequency IEC 61000-4-8 Voltage dips and interruptions immunity test IEC 61000-4-11 Emission tests FCC Part 15 class A
Overvoltage category	III

Ordering and shipping details

Category	09734-EASYLOGIC METERS AND ACCESSORIES
Discount Schedule	PL1
GTIN	3606480800160
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.70 in (11.94 cm)
Package 1 Width	4.70 in (11.94 cm)
Package 1 Length	3.60 in (9.14 cm)
Package 1 Weight	0.82 lb(US) (0.37 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information