

Part Number : 2157601016

Product Description : Micro-Fit+ Versa Color Right-Angle Header, Through Hole, 3.00mm Pitch, Single Row, 6 Circuits, Matte Tin (Sn) Plating, Glow-Wire Capable, Natural

Series Number : 215760

Status : Active

Product Category : PCB Headers and Receptacles

Documents & Resources

Drawings Drawing 2157601016_sd.pdf

3D Models and Design Files 3D Model 2157601016_stp.zip

Specifications

Application Specification 2064600001-AS-000.pdf Product Specification 2064600000-PS-000.pdf Test Summary 2157590005-TS-000.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Compliant with Exemption 44; 33 |
|--------------------|---|
| China RoHS | ® |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2023)3788-DC (14 Jun 2023) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents



- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|---|
| Category | PCB Headers and Receptacles |
| Series | 215760 |
| Description | Micro-Fit+ Versa Color Right-Angle Header, Through Hole, 3.00mm Pitch, Single Row, 6 Circuits, Matte Tin (Sn) Plating, Glow-Wire Capable, Natural |
| Application | Power, Wire-to-Board |
| Component Type | PCB Header |
| Product Family | Micro-Fit+ Connector System |
| Product Name | Micro-Fit+ Versa Color |
| UPC | 196823367359 |

Agency

| CSA | LR19980 |
|-----|---------|
|-----|---------|

Electrical

| Current - Maximum per Contact | 13.0A |
|-------------------------------|------------------|
| Voltage - Maximum | 600V AC (RMS)/DC |

Physical

| Breakaway | No |
|--------------------------------|-----------------|
| Circuits (Loaded) | 6 |
| Circuits (maximum) | 6 |
| Color - Resin | Natural (White) |
| Durability (mating cycles max) | 25 |
| First Mate / Last Break | No |

| Flammability | 94V-0 |
|--------------------------------|------------------------|
| Glow-Wire Capable | Yes |
| Keying to Mating Part | Yes |
| Lock to Mating Part | Yes |
| Material - Metal | High Copper Alloy |
| Material - Plating Mating | Matte Tin |
| Material - Plating Termination | Matte Tin |
| Material - Resin | Liquid Crystal Polymer |
| Net Weight | 1.054/g |
| Number of Rows | 1 |
| Orientation | Right Angle |
| Packaging Type | Тгау |
| PC Tail Length | 3.17mm |
| PCB Retention | Yes |
| PCB Thickness - Recommended | 1.57mm |
| Pitch - Mating Interface | 3.00mm |
| Pitch - Termination Interface | 3.00mm |
| Polarized to Mating Part | Yes |
| Polarized to PCB | Yes |
| Shrouded | Yes |
| Temperature Range - Operating | -40° to +105°C |
| Termination Interface Style | Through Hole |

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|--|---------------|
| Micro-Fit+ Single Row Receptacle Housings | <u>215759</u> |

This document was generated on Jan 11, 2024