## Product data sheet Characteristics

# XB5AD912R10K

Complete potentiometer, Harmony XB5, plastic, 22mm, 10K





Main	
Range of Product	Harmony XB5
Product or Component Type	Potentiometer
Device short name	XB5
Head type	Standard
Device presentation	Complete product

Com	പപ	mon	toni
COIII	ושוע	HEI	ılaı y

Bezel material	Dark grey plastic
Mounting diameter	0.87 in (22 mm)
Product Compatibility	Ø 6 mm shaft
Sale per indivisible quantity	1
CAD overall width	1.18 in (30 mm)
CAD overall height	1.65 in (42 mm)
CAD overall depth	3.23 in (82 mm)
Product Weight	0.11 lb(US) (0.048 kg)
Protective treatment	TH
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Ambient Air Temperature for Operation	-40158 °F (-4070 °C)
Electrical shock protection class	Class II IEC 60536
IP degree of protection	IP66 IEC 60529
NEMA degree of protection	NEMA 13 NEMA 4X
Resistance to high pressure washer	1015.26 psi (7000000 Pa) 131 °F (55 °C) 0.1 m
IK degree of protection	IK03 IEC 50102
	004 000 0 1 44
Standards	CSA C22.2 No 14 UL 508 EN/IEC 60947-1
Product Certifications	UL 508
	UL 508 EN/IEC 60947-1 BV CSA
Product Certifications	UL 508 EN/IEC 60947-1 BV CSA UL Listed
Product Certifications  Shape of signaling unit head	UL 508 EN/IEC 60947-1 BV CSA UL Listed Round
Product Certifications  Shape of signaling unit head  Operator profile	UL 508 EN/IEC 60947-1  BV CSA UL Listed  Round  Knurled knob, with white)  <= 42 V DC
Product Certifications  Shape of signaling unit head  Operator profile  [Us] rated supply voltage	UL 508 EN/IEC 60947-1  BV CSA UL Listed  Round  Knurled knob, with white)  <= 42 V DC <= 30 V AC
Product Certifications  Shape of signaling unit head  Operator profile  [Us] rated supply voltage  Rated power in W	UL 508 EN/IEC 60947-1  BV CSA UL Listed  Round  Knurled knob, with white)  <= 42 V DC <= 30 V AC  1 W 158 °F (70 °C)
Product Certifications  Shape of signaling unit head  Operator profile  [Us] rated supply voltage  Rated power in W  Precision of internal conversion resistor	UL 508 EN/IEC 60947-1  BV CSA UL Listed  Round  Knurled knob, with white)  <= 42 V DC <= 30 V AC  1 W 158 °F (70 °C) +-10%
Product Certifications  Shape of signaling unit head  Operator profile  [Us] rated supply voltage  Rated power in W  Precision of internal conversion resistor  Potentiometer characteristic	UL 508 EN/IEC 60947-1  BV CSA UL Listed  Round  Knurled knob, with white)  <= 42 V DC <= 30 V AC  1 W 158 °F (70 °C) +-10%  Linear
Product Certifications  Shape of signaling unit head  Operator profile  [Us] rated supply voltage  Rated power in W  Precision of internal conversion resistor  Potentiometer characteristic  Mechanical durability	UL 508 EN/IEC 60947-1  BV CSA UL Listed  Round  Knurled knob, with white)  <= 42 V DC <= 30 V AC  1 W 158 °F (70 °C) +-10%  Linear  50000 cycles
Product Certifications  Shape of signaling unit head  Operator profile  [Us] rated supply voltage  Rated power in W  Precision of internal conversion resistor  Potentiometer characteristic  Mechanical durability  Ohmic value	UL 508 EN/IEC 60947-1  BV CSA UL Listed  Round  Knurled knob, with white)  <= 42 V DC <= 30 V AC  1 W 158 °F (70 °C) +-10%  Linear  50000 cycles  10000 Ohm

Main group	Potentiometer
Group of product	Potentiometer knurled knob
Colour of marking	White

### Ordering and shipping details

Category	22468-PUSHBUTTONS,22MM(METAL) NEW
Discount Schedule	CS2
GTIN	3606480985072
Returnability	Yes
Country of origin	FR

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.65 in (4.2 cm)
Package 1 Width	2.20 in (5.6 cm)
Package 1 Length	3.31 in (8.4 cm)
Package 1 Weight	2.08 oz (59.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Height	5.91 in (15 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	5.90 lb(US) (2.678 kg)

#### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS  Declaration
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.