Ground Fault Products Heavy Duty Commercial Weather Resistant

GFCI Receptacles

Features

- Patented AUTOGUARD® self test technology
- Meets NEC requirements for weather resistance (406.9), UV and corrosion resistance for harsh and damp applications
- Protects against line and load reversal, no power to the face or downstream if device is miswired
- Single LED status indicator green indicates power, red indicates a trip, flashing red indicates end of life

Ordering Information

Description 20A, 125V, Style Line®, AUTOGUARD® self test GFCI receptacle, weather resistant, flush face, back and side wired, tri-drive screws

Color Black **UPC** 883778999772 Catalog Number GFRWR20BLK



HUBBELL

Listings

UL Listed - Canadian and U.S. UL 943 Class A for GFCIs UL File E41978 Meets ADA Standards Meets all NEC® and CEC requirements CSA Certified NEMA® WD-6 ANSI 73 Compliant

Specifications

Face Nylon Base Nylon **Power Contacts Brass Ground Contacts** Brass

Mounting Strap Zinc plated steel Mounting Screws Zinc plated steel Auto-Ground Staple Stainless steel

Performance

Electrical

Current Interrupting Dielectric Voltage

Withstands 1,500V minimum Trip Level

4 to 6 mA

Trip Time .025 second nominal

Frequency 60 Hz

Voltage 120V AC +10% - 15% (102V to 132V)

Amperage 15A/20A, 20A Feed Thru

Maximum Interrupting Capacity 10,000A

Mechanical

Ratings are a permanent part of the device Product Identification #14-#10 AWG copper stranded or solid **Terminal Accommodation**

conductor only

Certified for current interrupting at full rated

Terminal Identification Terminals identified in accordance with UL

498 and CSA

Environmental

UI 94V-2 Flammability

Operating Temperature -35°C to 66°C or -30°F to 150°F

Accessories

Wallplates for duplex openings Solid Right Angle Pigtailed Terminal SNAP1RA Stranded Right Angle Pigtailed Terminal SNAP2RA

Online Resources

Customer Use Drawing eCatalog Installation Instructions

