

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13
- 14
- 15
- 16
- 17
- 18

**MATERIAL**

High-resilience polyamide based (PA) technopolymer, black colour, matte finish.

**ROTATING PIN**

AISI 303 stainless steel.

**STANDARD EXECUTIONS**

- **CFE-B**: nickel-plated brass bosses with threaded hole.
- **CFE-p**: nickel-plated steel threaded studs.
- **CFE-CH**: pass-through holes for cylindrical head screws.
- **CFE-B-p**: nickel-plated brass bosses with threaded hole and nickel-plated steel threaded studs.
- **CFE-B-CH**: nickel-plated brass bosses with threaded hole and pass-through holes for cylindrical head screws.
- **CFE-p-CH**: nickel-plated steel threaded studs and pass-through holes for cylindrical head screws.

**APPLICATIONS**

This hinge has been developed in particular for doors provided with gaskets.

**ROTATION ANGLE (APPROXIMATE VALUE)**


Max 200° (-80° and +120° being 0° the condition where the two interconnected surfaces are on the same plane).

Do not exceed the rotation angle limit so as not to prejudice the hinge mechanical performance.

To choose the convenient type and the right number of hinges for your application, see the Guidelines (see page 1298).




FMM design



Description	AXIAL STRESS		RADIAL STRESS		90° ANGLED STRESS	
	Maximum working load Ea [N]	Load at breakage Ra [N]	Maximum working load Er [N]	Load at breakage Rr [N]	Maximum working load E90 [N]	Load at breakage R90 [N]
CFE.30 B-M3	50	660	140	1040	50	310
CFE.30 p-M3x13	40	460	110	1040	60	560
CFE.30 CH-3	50	640	120	980	20	300
CFE.30 B-M3-p-M3x13	40	460	110	1040	50	310
CFE.30 B-M3-CH-3	50	640	120	980	20	300
CFE.30 p-M3x13-CH-3	40	460	110	980	20	300
CFE.40 B-M4	90	1110	230	1920	60	590
CFE.40 p-M4x18	90	1110	300	2440	60	590
CFE.40 CH-4	150	1580	370	2460	80	1210
CFE.40 B-M4-p-M4x18	90	1110	230	1920	60	590
CFE.40 B-M4-CH-4	90	1110	230	1920	60	590
CFE.40 p-M4x18-CH-4	90	1110	300	2440	60	590
CFE.48 B-M5	160	1260	440	2890	190	1290
CFE.48 p-M5x17	190	1900	310	2870	160	1190
CFE.48 CH-5	300	2160	410	2850	150	1440
CFE.48 B-M5-p-M5x17	160	1260	310	2870	160	1190
CFE.48 B-M5-CH-5	160	1260	410	2850	150	1290
CFE.48 p-M5x17-CH-5	190	1900	310	2850	150	1190
CFE.66 B-M6	530	4160	500	2480	310	2250
CFE.66 p-M6x16	240	2670	700	3490	270	1830
CFE.66 CH-6	440	3160	690	3450	260	2920
CFE.66 B-M6-p-M6x16	240	2670	500	2480	270	1830
CFE.66 B-M6-CH-6	440	3160	500	2480	260	2250
CFE.66 p-M6x16-CH-6	240	2670	690	3450	260	1830

Hinges and accessories



Code	Description	L	B	d1	h	d2	l	f <sub>±0.25</sub>	f1 ±0.25	H	h1	b1	d	d3	d5	C [Nm] B#	C [Nm] p#	C [Nm] CH#	△
423111	CFE.30 B-M3	30.5	45.5	M3	4	-	-	15	30	12.5	9.5	15	2.5	-	-	1	-	-	11
423121	CFE.30 p-M3x13	30.5	45.5	-	-	M3	13	15	30	12.5	9.5	15	2.5	-	-	-	1	-	14
423131	CFE.30 CH-3	30.5	45.5	-	-	-	-	15	30	12.5	9.5	15	2.5	3.5	6	-	-	0.5	8
423141	CFE.30 B-M3-p-M3x13	30.5	45.5	M3	4	M3	13	15	30	12.5	9.5	15	2.5	-	-	1	1	-	13
423151	CFE.30 B-M3-CH-3	30.5	45.5	M3	4	-	-	15	30	12.5	9.5	15	2.5	3.5	6	1	-	0.5	10
423161	CFE.30 p-M3x13-CH-3	30.5	45.5	-	-	M3	13	15	30	12.5	9.5	15	2.5	3.5	6	-	1	0.5	11
423211	CFE.40 B-M4	40.5	59	M4	5.5	-	-	20	40.4	16.5	12.5	20	4	-	-	4	-	-	26
423221	CFE.40 p-M4x18	40.5	59	-	-	M4	18	20	40.4	16.5	12.5	20	4	-	-	-	2	-	34
423231	CFE.40 CH-4	40.5	59	-	-	-	-	20	40.4	16.5	12.5	20	4	4.5	7.5	-	-	1	19
423241	CFE.40 B-M4-p-M4x18	40.5	59	M4	5.5	M4	18	20	40.4	16.5	12.5	20	4	-	-	4	2	-	30
423251	CFE.40 B-M4-CH-4	40.5	59	M4	5.5	-	-	20	40.4	16.5	12.5	20	4	4.5	7.5	4	-	1	21
423261	CFE.40 p-M4x18-CH-4	40.5	59	-	-	M4	18	20	40.4	16.5	12.5	20	4	4.5	7.5	-	2	1	26
423311	CFE.48 B-M5	48.5	70	M5	6.5	-	-	24	46	20	15	24	5	-	-	5	-	-	44
423321	CFE.48 p-M5x17	48.5	70	-	-	M5	17	24	46	20	15	24	5	-	-	-	5	-	58
423331	CFE.48 CH-5	48.5	70	-	-	-	-	24	46	20	15	24	5	5.5	9	-	-	2	31
423341	CFE.48 B-M5-p-M5x17	48.5	70	M5	6.5	M5	17	24	46	20	15	24	5	-	-	5	5	-	51
423351	CFE.48 B-M5-CH-5	48.5	70	M5	6.5	-	-	24	46	20	15	24	5	5.5	9	5	-	2	38
423361	CFE.48 p-M5x17-CH-5	48.5	70	-	-	M5	17	24	46	20	15	24	5	5.5	9	-	5	2	45
423411	CFE.66 B-M6	66	97	M6	10	-	-	33	63.7	27.5	21	33	6	-	-	5	-	-	103
423421	CFE.66 p-M6x16	66	97	-	-	M6	16	33	63.7	27.5	21	33	6	-	-	-	5	-	124
423431	CFE.66 CH-6	66	97	-	-	-	-	33	63.7	27.5	21	33	6	6.5	10.5	-	-	5	77
423441	CFE.66 B-M6-p-M6x16	66	97	M6	10	M6	16	33	63.7	27.5	21	33	6	-	-	5	5	-	115
423451	CFE.66 B-M6-CH-6	66	97	M6	10	-	-	33	63.7	27.5	21	33	6	6.5	10.5	5	-	5	90
423461	CFE.66 p-M6x16-CH-6	66	97	-	-	M6	16	33	63.7	27.5	21	33	6	6.5	10.5	-	5	5	100

# Suggested tightening torque for assembly screws.

