

# collaborative robot, Lexium Cobot, maximum payload 18kg

LXMRL18S0000

Product availability: Stock - Normally stocked in distribution facility

Price\*: 40,800.00 USD

### Main

Range of Product	Lexium Cobot	
Product or Component Type	Collaborative robot	
maximum payload	39.7 lb(US) (18 kg)	
operating radius	42.2 in (1073 mm)	
positioning accuracy	+/- 0.02 mm	
degree of freedom	6	
programming	Graphical drag & drop	
teach-in device	lpad ios app Android app	

## Complementary

oompromentary		
maximum speed	120°/s joint 1 +/- 360°	
	120°/s joint 2 -85, +265°	
	180°/s joint 3 +/- 175°	
	180°/s joint 4 -85, +265°	
	180°/s joint 5 +/- 360°	
	180°/s joint 6 +/- 360°	
Rated voltage	24 V	
digital input number	2	
digital output number	2	
Analogue input number	2	
Power Consumption in W	600 W	
Mounting position	Any position	
screw type	M8	
Standards	GB 11291.1:2011	
	EN/ISO 10218-1:2011	
	EN 60204-1:2018	
	EN/ISO 12100:2010	
	EN/ISO 13849-1:2015	
	EN 61000-6-2:2005	
	EN 61000-6-4:2007+A1:2011	
	ISO 13849-1:2015	
	ISO 13849-2:2012	
	ISO 14644-1	
	ISO 9001:2015	
	UL 1740	
	ANSI/RIA R15.06	
	CAN/CSA Z434	
	NFPA 79	
	CAN/CSA C22.2 No. 24	
	REACH	
	RoHS	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Marking	CE KC TÜV
Material	Aluminium
base diameter	7.4 in (188 mm)
Cable length	19.7 ft (6 m)
Product Weight	77.2 lb(US) (35 kg)

## **Environmental**

IP Degree of Protection	IP54
Ambient air temperature for operation	32122 °F (050 °C)

# Ordering and shipping details

Category	US1PC5418307
Discount Schedule	PC54
GTIN	3606485859514
Returnability	Yes
Country of origin	CN

# **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	20.28 in (51.5 cm)	
Package 1 Width	20.67 in (52.5 cm)	
Package 1 Length	30.12 in (76.5 cm)	
Package 1 Weight	87.7 lb(US) (39.8 kg)	
Unit Type of Package 2	P12	
Number of Units in Package 2	4	
Package 2 Height	41.34 in (105 cm)	
Package 2 Width	31.50 in (80 cm)	
Package 2 Length	47.24 in (120 cm)	
Package 2 Weight	410.5 lb(US) (186.2 kg)	



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability

Environmental footp	rint

Environmental Disclosure

Product Environmental Profile

### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No